



# ABC-170CE

Dual Channel Cycling Station with Extended Sink Power



## The Ideal CE Certified System for Fuel Cells Testing

AeroVironment's ABC-170CE is used internationally to develop and test products that require additional sinking power. The ABC-170CE was originally developed to test fuel cells in an energy efficient manner by returning clean AC power back to the utility grid. AeroVironment's customers now use this versatile machine to test batteries, hybrids and other electric vehicle (EV) and hybrid electric vehicle (HEV) applications that require higher discharging capability. All AV power cycling systems are equipped with a real-time clock on the system's control board that enables accurate measurement of Ah and kWh during cycling.

## APPLICATION GUIDE

Battery Testing and Cycling	Battery Module	
	Battery Management System (BMS)	•
	Battery Pack	•
	Production Testing	•
Simulation	Battery	•
	Powertrain	•
	Fuel Cell	•
	Hardware in the Loop	•
Energy Storage Charging and Testing	Fuel Cell	•
	Super & Ultra Capacitors	•
	Flywheels	•
Power Generation Equipment Testing	Electric Components	•
	Power Supplies	•
	Generators	•
	Stationary Power	•
	Inverters	•
	Military & Aerospace	•
	Life, Run-in, Burn-in	•
Uninterruptable Power Supplies (UPS)	•	
Hybrid and Electric Vehicle, End-of-line Testing	Powertrain	•
	Production Testing	•
	Medium & Heavy-duty (buses, trams, trolleys, trucks, trains)	•

## SPECIFICATIONS



INPUT RATING	3 Phase, 415Vrms (380Vrms, 400Vrms, 440Vrms, 480Vrms options)
CURRENT	213Arms at 415Vrms
FREQUENCY	50Hz (60 Hz optional)
ISOLATION TRANSFORMER	Internal transformer
POWER FACTOR	> 99%
HARMONIC DISTORTION	< 3% THD; IEEE 519 Compliant
MULTIPLE USER INTERFACES	Manual; Remote Operation System (ROS); DCOM Driver for LabVIEW; C++ and Visual Basic; CAN
WEIGHT	3400 lbs (1542 kg)
DIMENSIONS	73"W x 71"H x 30"D (183cm W x 180cm H x 76cm D)

## OPERATING RANGE

CONFIGURATION	VOLTAGE (Vdc)	CURRENT (Adc)	POWER (kW)
INDEPENDENT	+8 to +420	-320 to +265	-170 to +125
OPTIONAL RANGE	+420 to +435	-160 to +160	-70 to +70
	+435 to +445	-90 to +90	-40 to +40
PARALLEL	+8 to +420	-640 to +530	-170 to +125

© 2017 AeroVironment, Inc. 052317

Some features are only available with appropriate software. For further info, please contact AV at p3sales@avinc.com. All specifications are subject to change. Trademark usage in image shown may vary slightly.

